Features:

- ◆ Metal IR Dome IP Camera
- ◆ IR LED: 1 pcs IR-III Led, IR Range: 25M
- ◆ Video Output: 1 x RJ45 port, wifi Optional
- ◆ Support Onvif, Support Gmail/GOOGLE/QQ/EMAIL
- ◆ OSD, Motion Detection, Remote View and Control, IR-Cut
- ◆ Working Temperature: -10℃~ +60℃
- ◆ Size: 75mm ×55mm
- ◆ Weight: 750g

Specifications

Model ID	VN-IHB10H	VN-IHB10	VN-IHB13H	VN-IHB13E	VN-IHB13	VN-IHB20E	VN-IHB20C	VN-IHB20	VN-IHB20D	VN-IHB30
Description	Metal IR Dome IP Camera,IR LED: 1 pcs IR-III Led, IR Range: 25M									
TV System	NTSC / PAL									
Video Output	1 x RJ45 port									
Chipset Solution	1/4" XM H42 + Hi3518E 1.0 Mega Pixels CMOS	1/4" OV 9712+HI3518E 1.0 Mega Pixels CMOS	1/3" XM H81 + Hi3518E 1.3 Mega Pixels CMOS	1/3" Aptina AR0130 + Hi3518E 1.3 Mega Pixels CMOS	1/3" Aptina AR0130 + Hi3518C 1.3 Mega Pixels CMOS	1/3" XM SC2035 + Hi3518E 2 Mega Pixels CMOS	1/3" XM SC2035 + Hi3516C 2 Mega Pixels CMOS	1/2.5" Sony IMX323 + Hi3516C 2 Mega Pixels CMOS	1/3" Aptina AR0237 + Hi3516D 2 Mega Pixels CMOS	1/3" AR0330 + Hi3516D 3 Mega Pixels CMOS
Resolution	720P@ 25fps(PAL), 30fps(NTSC)	720P@ 25fps(PAL), 30fps(NTSC)	960P @ 25fps(PAL), 30fps(NTSC)	960P @ 25fps(PAL), 30fps(NTSC)	960P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	1080P @ 25fps(PAL), 30fps(NTSC)	3MP @ 25fps(PAL), 30fps(NTSC)
Effective Pixels	1920(H)×720(V)	1920(H)×720(V)	1920(H)×960(V)	1920(H)×960(V)	1920(H)×960(V)	1920(H)×1080(V)	1920(H)×1080(V)	1920(H)×1080(V)	1920(H)×1080(V)	2048(H)×1536(V)
Minimum Illumination	0.001Lux									
Lens	3.6mm(2M Pixels)									
	/	2.8/6/8mm (Optional)	/	2.8/6/8mm (Optional)	2.8/6/8mm (Optional)	2.8/6/8mm (Optional)	2.8/6/8mm (Optional)	2.8/6/8mm (Optional)	/	/
Sync,System	Internal Synchronization									
Network	1 RJ45 Ethernet interface, 10/100M adaptation									
Video Compression	H.264 compression								H.265 compression	
Protocol	Support Gmail/GOOGLE/QQ/EMAIL									
Onvif	Support Onvif									
S/N Ratio	≥ 58dB									
POE	Optional									
OSD	YES									
WIFI	/	/	/	/	Optional	/	/	Optional	/	/
Power Source	DC 12V/2A									
Consumption	<5W									
Operating Enviroment	-10℃~60℃ / 10% ~ 95%RH									
Working Humidity	≤90%									
Size(mm)	75mm ×55mm									
Weight(kg)	0.75 kg									