

## Features:

- ◆ 6x10/100Mbps auto-sensing RJ45 ports, 4x 10/100Mbps PoE ports, 2x uplink port;
- ◆ Supports port auto-flip (Auto MDI/ MDIX);
- ◆ External power supply;
- ◆ Maximum power of single PoE port: 15.4W/30W;
- ◆ Adopts store-and-forward architecture; IEEE 802.3af/at power on up to 4 ports;
- ◆ Features with fanless, natural cooling, small, compact and quiet design, suitable for desktop or wall;



Model		VD-204P
Power	Power Adapter Voltage	48-57V DC
	Consumption	65W/120W
Network Connector	Network Port	1~4 Port : 10/100Mbps POE Ethernet Port
		2*Uplink Port : 10/100Mbps Ethernet Port
	Transmission Distance	1~4 Port: Default: 0~100m (10/100Mbps)
		CCTV: 0~250m (10Mbps)
Transmission Medium	2*Uplink Port: 100m (100Mbps)	
Network Switch	Network Standard	IEEE 802.3/802.3u, IEEE 802.3x, IEEE 802.1p, IEEE 802.3az
	Switching Capacity	1.2Gbps
	Packet Forwarding Rate	0.8928Mpps
	MAC Table	2K
Power Over Ethernet	PoE Standard	IEEE 802.3af/at
	PoE Power Supply Type	End-Span(1/2+;3/6-)
	PoE Power Consumption	af≤45.4W, at≤30W (every port)
LED Status Indicator	PoE Ethernet LED Indicator	Power: 1 red light indicates that the power normal work;
		POE:4 yellow lights indicate that the POE is power on;
		Ethernet: 6 green lights indicate that the Ethernet link and act;
Environmental	Working temperature	-0°C~55°C
	Relative Humidity	20~95%
	Storage temperature	-20°C~70°C
Mechanical	Dimension (L×W×H)	135mm × 88mm × 27mm
	Color	Silver-Gray
	Weight	810g
Stability	MTBF	>30000h