

Features:

- ◆ 10 x 10/100Mbps auto-sensing RJ45 ports, 8x 10/100Mbps PoE ports, 2x 10/100/1000Mbps uplink port;
- ◆ Supports port auto-flip (Auto MDI/ MDIX);
- ◆ External power supply;
- ◆ Maximum power of single PoE port: 15.4W;
- ◆ Adopts store-and-forward architecture;
- ◆ IEEE 802.3af power on up to 8 ports;
- ◆ Features with fanless, natural cooling, small, compact and quiet design, suitable for desktop or wall;



Model		VD-208P
Power	Power Adapter Voltage	48-57V DC
	Consumption	120W
Network Connector	Network Port	1~8 Port : 10/100Mbps POE Ethernet Port
		2*Uplink Port : 10/100/1000Mbps Ethernet Port
	Transmission Distance	1~8 Port: Default: 0~100m (10/100Mbps)
		CCTV: 0~250m (10Mbps)
Transmission Medium	2*Uplink Port: 100m (100Mbps), Cat5/5e/6 standard network cable	
Network Switch	Network Standard	IEEE802.3az,IEEE802.3ah,IEEE1588,IEEE802.3x
		IEEE802.3,IEEE802.1as,IEEE802.1D
	Switching Capacity	5.6Gbps
	Packet Forwarding Rate	4.1664Mpps
MAC Table	16K	
Power Over Ethernet	PoE Standard	IEEE 802.3af
	PoE Power Supply Type	End-Span(1/2+/3/6-)
	PoE Power Consumption	af≤15.4W (every port)
LED Status Indicator	PoE Ethernet LED Indicator	Power: 1 red light indicates that the power normal work;
		POE: 8 yellow lights indicate that the POE is power on;
		Ethernet: 10 green lights indicate that the Ethernet link and
Environmental	Working temperature	0°C~55°C
	Relative Humidity	20~95%
	Storage temperature	-20°C~70°C
Mechanical	Dimension (L×W×H)	207mm × 95mm × 27mm
	Color	Silver-Gray
	Weight	1300g
Stability	MTBF	>30000h