

Features:

- ◆ 5x 10/100Mbps auto-sensing RJ45 ports, 4x 10/100Mbps PoE ports, 1x uplink port
- ◆ Supports port auto-flip (Auto MDI/ MDIX);
- ◆ Build-in power supply;
- ◆ Maximum power of single PoE port: 15.4W;
- ◆ Adopts store-and-forward architecture;
- ◆ IEEE 802.3af power on up to 4 ports;



Model		VD-204PG
Power	Power Adapter Voltage	AC100-240V
	Consumption	65W, build-in power supply;
Network Connector	Network Port	1~4 Port : 10/100Mbps POE Ethernet Port Uplink Port:10/100Mbps Ethernet Port
	Transmission Distance	1~4 Port: 0 ~ 100m Uplink Port: 0 ~ 100m
	Transmission Medium	Cat5/5e/6 standard network cable
Network Switch	Network Standard	IEEE 802.3/802.3u, IEEE 802.3x, IEEE 802.1p, IEEE 802.3az
	Switching Capacity	1Gbps
	Packet Forwarding Rate	0.7444Mpps
	MAC Table	2K
Power Over Ethernet	PoE Standard	IEEE 802.3af
	PoE Power Supply Type	End-Span(1/2+;3/6-)
	PoE Power Consumption	af≤15.4W (every port)
LED Status Indicator	PoE Ethernet LED Indicator	Power: 1 red light indicates that the power normal work; POE: 4 yellow lights indicate that the POE is power on; Ethernet: 5 green lights indicate that the Ethernet link and
Environmental	Working temperature	0℃~55℃
	Relative Humidity	20~95%
	Storage temperature	-20℃~70℃
Mechanical	Dimension (L×W×H)	188mm*120mm*35mm
	Color	Silver-Gray
	Weight	920g
Stability	MTBF	>30000h