

Features:

- ◆ 16x 10/100Mbps downlink PoE Ethernet Ports, 2x 10/100/1000Mbps uplink Ethernet Ports ;
- ◆ Supports port auto-flip (Auto MDI/ MDIX);
- ◆ Each of 16 ports all support IEEE802.3af/at;
- ◆ Maximum power per port: 15.4W/30W;
- ◆ Maximum PoE power: 250W/450W;
- ◆ Adopts store-and-forward architecture;



Model		VD-216P
Power	Power Adapter Voltage	AC100-240V
	Consumption	250W / 450W
Network Connector	Network Port	1~16 Port : 10/100Mbps POE Ethernet port Uplink Port : 10/100/1000Mbps Ethernet port
	Transmission Distance	1~16 Port : 0 ~ 100m Uplink Port : 0 ~ 100m
	Transmission Medium	Cat5/5e/6 standard network cable
	Network Standard	IEEE802.3/802.3u,IEEE802.3x,IEEE802.1D
Network Switch	Switching Capacity	11.2Gbps
	Packet Forwarding	8.3328Mpps
	MAC Table	4K
	PoE Standard	IEEE 802.3af/at
Power Over Ethernet	PoE Power Supply Type	End-Span(1/2+;3/6-)
	PoE Power Consumption	af≤15.4W,at≤30W (every one)
	LED Status Indicator	Power: 1 red light indicates that the power normal work; POE: 16 yellow lights indicate that the POE is power on; Ethernet:18 green lights indicate that the Ethernet Link and Act;
Environmental	Working temperature	0°C~55°C
	Relative Humidity	20~95%
	Storage temperature	-20°C~70°C
Mechanical	Dimension (L×W×H)	440mm*290mm*44mm
	Color	Silver-Gray
	Weight	4800g
Stability	MTBF	>30000h