

Features:

- ◆ 16x 10/100Mbps downlink PoE Ethernet Ports, 2x 10/100/1000Mbps uplink Ethernet Ports and 2x 1000Mbps uplink SFP Ports;
- ◆ Supports port auto-flip (Auto MDI/ MDIX);
- ◆ Each of 16 ports all support IEEE802.3af/at;
- ◆ Maximum power per port: 15.4W/30W;
- ◆ Maximum PoE power: 250W/450W;
- ◆ Adopts store-and-forward architecture;
- ◆ Built-in 1U rack power supply series, easy installation.



Model		VD-216PG
Power	Power Adapter Voltage	AC100-240V
	Consumption	250W / 450W
Network Connector	Network Port	1~16 Port : 10/100Mbps POE Ethernet port
		Uplink Port : 10/100/1000Mbps Ethernet port
		Uplink Port : 1000Mbps SFP Port
	Transmission Distance	1~16 Port : 0 ~ 100m
		Uplink Port : 0 ~ 100m
SFP: depends on the optical module		
Transmission Medium	Cat5/5e/6 standard network cable	
Network Switch	Network Standard	IEEE802.3/802.3u,IEEE802.3x,IEEE802.1D
	Switching Capacity	11.2Gbps
	Packet Forwarding	8.3328Mpps
	MAC Table	4K
Power Over Ethernet	PoE Standard	IEEE 802.3af/at
	PoE Power Supply Type	End-Span(1/2+/3/6-)
	PoE Power Consumption	af≤15.4W,at≤30W (every one)
LED Status Indicator	PoE Ethernet LED Indicator	Power: 1 red light indicates that the power normal work;
		POE: 16 yellow lights indicate that the POE is power on;
		Ethernet:18 green lights indicate that the Ethernet Link and Act;
Environmental	Working temperature	0°C~55°C
	Relative Humidity	20~95%
	Storage temperature	-20°C~70°C
Mechanical	Dimension (L×W×H)	440mm × 290mm × 44mm
	Color	Silver-Gray
	Weight	4800g
Stability	MTBF	>30000h