

Features:

- ◆ 3.5" Plastic Dome Camera
- ◆ LED: White 4pcs, Range: 20M
- ◆ Night Vision full color
- ◆ 50PCS Per Carton
- ◆ Size: φ108mm x 98mm
- ◆ Weight: 290g



Specifications

| Model ID | VD-ITB20FHD | VD-ITB40ZHD | VD-ITB50SHD |
|----------------------|--|---|---|
| Description | 3.5" Plastic Dome Camera,LED: White 4pcs, Range: 20M | | |
| TV System | NTSC / PAL | | |
| Video Out | BNC 4 in 1(AHD, TVI, CVI, CVBS Switch by OSD) | | |
| Chipset Solution | 1/3" 1080P 2MP CMOS Sensor S291+ FH8536H Low illum | 1/2.7" 4MP CMOS Sensor GC2053 + FH8536H Low illum | 1/2.7" 5MP CMOS Sensor IMX335 + FH8558M Low illum |
| Resolution | 1080P@ 25fps(PAL), 30fps(NTSC) | 4MP@ 25fps(PAL), 30fps(NTSC) | 5MP@ 25fps(PAL), 30fps(NTSC) |
| Effective Pixels | 1920(H)×1080(V) | 2688(H)×1520(V) | 2560(H)×1920(V) |
| Minimum Illumination | 0.001Lux | | |
| Lens | 2.8/6/8mm Optional | | |
| | 3.6mm Board Lens | | |
| Sync.System | Internal Synchronization | | |
| Scanning System | 2:1 Interface | | |
| Shutter Speed | 1/60~1/100,000sec (N), 1/50~1/100,000sec (P) | | |
| S/N Ratio | ≥ 58dB | | |
| DWDR | YES | | |
| OSD | NO | Optional | YES |
| UTC | YES | | |
| 3D-NR | YES | | |
| Power Source | DC12V ±10% | | |
| Consumption | <5W | | |
| Operating Enviroment | -20℃~60℃ / 10% ~ 95%RH | | |
| Working Humidity | ≤90% | | |
| Size(mm) | φ108mm x 98mm | | |
| Weight(kg) | 0.29 Kg | | |