

Features:

- ◆ Waterproof Metal Full Color Bullet IP Camera
- ◆ Water Resistance: IP66
- ◆ IR LED: 4pcs White Led, 4PCS IR Leds, Night Vision full color
- ◆ Video Output: 1 x RJ45 port
- ◆ Support Onvif, Support Gmail/GOOGLE/QQ/EMAIL
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ OSD, Motion Detection, Remote View and Control, IR-Cut
- ◆ Working Temperature: -10°C ~ +60°C
- ◆ 24PCS Per Carton
- ◆ Size: 235mm x75mm x68mm
- ◆ Weight:930g



Specifications

Model ID	VN-NV20	VN-NV40K	VN-NV50K	VN-NV50S	VN-NV80
Description	Waterproof Metal Full Color Bullet IP Camera,IR LED: 4pcs White Led, 4PCS IR Leds, Night Vision full color				
TV System	NTSC / PAL				
Video Output	1 x RJ45 port				
Chipset Solution	1/2.8" 2.0 MP Starvis SONY307 + GK7205V200	1/3" 4.0 MP Low illum SC5239S + GK7205V210	1/2.8" 5.0 MP Low illum SC5239S + GK7605V100	1/2.8" 5.0 MP Starvis SONY 335 + GK7205V300	1/2.7" 8.0 MP Low illum SC8239 + NT98566
Resolution	2MP, 720P	4MP, 1080P	5MP, 3MP/1080P	5MP, 3MP/1080P	8MP, 5MP/1080P
Effective Pixels	1920(H)×1080(V)	2560(H)×1440(V)	2592(H)×1944(V)	2592(H)×1944(V)	3840(H)×2160(V)
Minimum Illumination	0.001Lux				
Lens	3MP 2.8-12mm Manual Zoom Lens Optional (9-22mm Lens)	5MP 2.8-12mm Manual Zoom Lens	5MP 2.8-12mm Manual Zoom Lens	5MP 2.8-12mm Manual Zoom Lens	8MP 2.8-12mm Manual Zoom Lens
Sync_System	Internal Synchronization				
Network	1 RJ45 Ethernet interface, 10/100M adaptation				
Video Compression	H.265				
Protocol	Support Gmail/GOOGLE/QQ/EMAIL				
Onvif	Support Onvif				
S/N Ratio	≥ 58dB				
Audio	Optional				
AI Defog	YES				
AI humanoid Detection	YES				
POE	External PoE (Optional)				
OSD	YES				
3D DNR	YES				
D-WDR	YES				
Power Source	DC 12V/2A				
Consumption	<5W				
Operating Enviroment	-10°C~60°C / 10%~95%RH				
Working Humidity	≤90%				
Size(mm)	235mm x 75mm x 68mm				
Weight(kg)	0.93 kg				