

Features:

- ◆ Waterproof IR Bullet IP Camera
- ◆ Water Resistance: IP66
- ◆ IR LED: \varnothing 5X36pcs, IR Range: 30M
- ◆ Obscured glass, hidden IR Led
- ◆ Video Output: 1 x RJ45 port
- ◆ Support Onvif, Support Gmail/GOOGLE/QQ/EMAIL
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ OSD, Motion Detection, Remote View and Control, IR-Cut
- ◆ Working Temperature: $-10^{\circ}\text{C} \sim +60^{\circ}\text{C}$
- ◆ Size: 187mm x 65mm x 67mm
- ◆ Weight: 580g



Specifications

Model ID	VN-KB20	VN-KB40X	VN-KB40K	VN-KB50K	VN-KB50S	VN-KB80	VN-KB80T
Description	Waterproof IR Bullet IP Camera,Obscured glass, hidden IR Led,IR LED: \varnothing 5X36pcs, IR Range: 30M						
TV System	NTSC / PAL						
Video Output	1 x RJ45 port						
Chipset Solution	1/2.8" SONY IMX307 + GK7205V200	1/2.8" SC5239S + XM530V200	1/2.8" SC5239S + GK7205V210	1/2.8" SC5339S + GK7205V300	1/2.8" SONY335 + GK7205V300	1/2.8" SC8239 + NT98566	1/2.8" SONY IMX415 + NT98566
Resolution	2MP, 720P	4MP, 1080P	4MP, 1080P	5MP, 3MP/1080P	5MP, 3MP/1080P	8MP, 5MP/1080P	8MP, 5MP/1080P
Effective Pixels	1920(H) \times 1080(V)	2560(H) \times 1440(V)	2560(H) \times 1440(V)	2592(H) \times 1944(V)	2592(H) \times 1944(V)	3840(H) \times 2160(V)	3840(H) \times 2160(V)
Minimum Illumination	0.001Lux						
Lens	3.6mm Board Lens/2.8mm (Optional)						
Sync, System	Internal Synchronization						
Network	1 RJ45 Ethernet interface, 10/100M adaptation						
Video Compression	H.265 compression						
Protocol	Support Gmail/GOOGLE/QQ/EMAIL						
Onvif	Support Onvif						
SD Card Slot	/		Optional		/		Optional
3D DNR	YES						
D-WDR	YES						
AI Defog	YES						
AI humanoid Detection	YES						
Audio	Optional						
S/N Ratio	\geq 58dB						
POE	Optional(Built-in POE)						
Power Source	DC 12V/2A						
Consumption	<5W						
Operating Enviroment	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ / 10% ~ 95%RH						
Working Humidity	\leq 90%						
Size(mm)	187mm x 65mm x 67mm						
Weight(kg)	0.58 KG						