

Features:

- ◆ Waterproof IR Bullet IP Camera
- ◆ Water Resistance: IP66
- ◆ IR LED: \varnothing 5X30pcs, IR Range: 30M
- ◆ Video Output: 1 x RJ45 port,
- ◆ Support Onvif, Support Gmail/GOOGLE/QQ/EMAIL
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ OSD, Motion Detection, Remote View and Control, IR-Cut
- ◆ Working Temperature: $-10^{\circ}\text{C} \sim +60^{\circ}\text{C}$
- ◆ Size: 175mm x 69mm x 55mm
- ◆ Weight: 600g



Specifications

Model ID	VN-IB20	VN-IB40X	VN-IB40K	VN-IB50K	VN-IB50S	VN-IB80	VN-IB80T
Description	Waterproof IR Bullet IP Camera, IR LED: \varnothing 5X30pcs, IR Range: 30M						
TV System	NTSC / PAL						
Video Output	1 x RJ45 port						
Chipset Solution	1/2.8" SONY IMX307 + GK7205V200	1/2.8" SC5239S + XM530V200	1/2.8" SC5239S + GK7205V210	1/2.8" SC5339S + GK7205V300	1/2.8" SONY335 + GK7205V300	1/2.8" SC8239 + NT98566	1/2.8" SONY IMX415 + NT98566
Resolution	2MP, 720P	4MP, 1080P	4MP, 1080P	5MP, 3MP/1080P	5MP, 3MP/1080P	8MP, 5MP/1080P	8MP, 5MP/1080P
Effective Pixels	1920(H)×1080(V)	2560(H)×1440(V)	2560(H)×1440(V)	2592(H)×1944(V)	2592(H)×1944(V)	3840(H)×2160(V)	3840(H)×2160(V)
Minimum Illumination	0.001Lux						
Lens	3.6mm Board Lens/2.8mm (Optional)						
Sync, System	Internal Synchronization						
Network	1 RJ45 Ethernet interface, 10/100M adaptation						
Video Compression	H.265 compression						
Protocol	Support Gmail/GOOGLE/QQ/EMAIL						
Onvif	Support Onvif						
SD Card Slot	/		Optional		/		Optional
3D DNR	YES						
D-WDR	YES						
AI Defog	YES						
AI humanoid Detection	YES						
Audio	Optional						
S/N Ratio	$\geq 58\text{dB}$						
POE	Optional(Built-in POE)						
Power Source	DC 12V/2A						
Consumption	<5W						
Operating Enviroment	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$ / 10% ~ 95%RH						
Working Humidity	$\leq 90\%$						
Size(mm)	175mm x 69mm x 55mm						
Weight(kg)	0.6 KG						