

Features:

- ◆ 2.5" Mini IP66 Metal PTZ Camera
- ◆ Pan Range: 0°-355°, Pan Speed: Max 30°/sec
- ◆ Tilt Range: 90°, Tilt Speed: Max 30°/sec, Preset: 128
- ◆ IR Led: 42μ x3pcs, IR Range: 30M
- ◆ Support HD-TVI/HD-CVI/AHD/CVBS HD Video Output
- ◆ Support UTC Protocol, HIKVISION, DAHUA, XM, TVT DVR...
- ◆ Support Coaxial Cable Control for Pan, Tilt, Zoom, Focus, OSD
- ◆ Support English, Russian, Spanish, French, Italian, Greek, Portuguese, Chinese, Korean
- ◆ lightning-proof, surge-proof
- ◆ Size: 103mm x 98mm(H)
- ◆ Weight: 900g



Specification:

MODEL NO.	VP-BMV5X20HD	VP-BMV5X50HD
Description	2.5" Mini IP66 Metal PTZ Camera, IR Led: 42μ x3pcs, IR Range: 30M	
TV System	NTSC / PAL	
Image Sensor	1/3" CMOS 2.0 Mega	1/3" CMOS Sensor 5.0 Mega
Resolution	1/3" 2.0 MP CMOS SONY IMX307 + NVP2441H Low Illumination	1/3" 5.0 MP CMOS SONY IMX335 + 2477 CMOS Low Illumination
Effective Pixels	1920(H) × 1080(V)	2592(H)×1944(V)
Lens	5X Optical Zoom(2.7-13.5mm Lens)	
Minimum illumination	0.01Lux @(F1.6,AGC ON) ,0 Lux with IR	
Video interface	BNC	
Video bit rate	32kbps-16Mbps	
Day and night conversion	IR-Cut	
Electronic shutter	1/25s ~ 1/100000s	
D-WDR	Support	
DNR	2D/3D-DNR	
Mirror	YES	
BLC	YES	
MD	YES	
Pan Range	0—355°	
Tilt Range	0—90°	
Horizontal speed	Max 30°/ s	
Vertical speed	Max 30°/ s	
Preset	128	
Audio I/O	Optional	
Waterproof level	IP66	
Size	φ103mm x 98mm(H)	
Weight	900g	
Power	DC12V	
Work temperature	-30℃~60℃	
Vandsec Electronics Limited http://www.vandsec.com Email: info@vandsec.com		