

Features:

- ◆ 3.5" IP66 Vandalproof Medium Speed IR Dome PTZ
- ◆ Support TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP
- ◆ Support Onvif, Preset: 255
- ◆ lightning-proof, surge-proof, External PoE Optional(add \$6)
- ◆ 3pcs IR Array Led, IR Range: 30M
- ◆ Pan Range: 355°, Pan Speed: Max 30°/sec
- ◆ Tilt Range: 90°, Tilt Speed: Max 30°/sec
- ◆ Video Compression: H.265 Main Profile, MJPEG/JPEG Baseline
- ◆ Built-in Temperature Control
- ◆ Size: ϕ 103mm x 98mm(H)
- ◆ Weight: 900g



Specification:

MODEL NO.	VNP-BMV5X20HD	VNP-BMV5X50HD
Description	3.5" IP66 Vandalproof Medium Speed IR Dome PTZ,3pcs IR Array Led, IR Range: 30M	
TV System	NTSC / PAL	
Image Sensor	1/3" CMOS 2.0 Mega	1/3" CMOS Sensor 5.0 Mega
Resolution	1/3" GK7205 + SONY IMX307 Starlight 2.0 Mega Pixels CMOS, Low Illumination	1/3" GK7205 + SONY IMX335 5.0 Mega Pixels CMOS, Low Illumination
Effective Pixels	1920(H) × 1080(V)	2592(H)×1944(V)
Lens	5x Optical Zoom(2.7-13.5mm Lens)	
Minimum illumination	0.01Lux @(F1.6,AGC ON) ,0 Lux with IR	
Video interface	RJ45	
Video compression	H.265	
Signal model	60HZ:30fps	
Video bit rate	32kbps-16Mbps	
Day and night conversion	IR-Cut	
Electronic shutter	1/25s ~ 1/100000s	
D-WDR	Support	
DNR	2D/3D-DNR	
Mirror	YES	
BLC	YES	
MD	YES	
POE	Optional	
Onvif	YES	
Pan Range	0—355°	
Tilt Range	0—90°	
Horizontal speed	Max 30°/ s	
Vertical speed	Max 30°/ s	
Preset	255	
Waterproof level	IP66	
Size	ϕ 103mm x 98mm(H)	
Weight	900g	
Power	DC12V	
Work temperature	-30°C~60°C	
Vandsec Electronics Limited http://www.vandsec.com Email: info@vandsec.com		