

Features:

- ◆ 4.5" IP66 Plastic Medium Speed IR Dome PTZ
- ◆ Support TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, PPPOE, SMTP, UPNP
- ◆ Support Onvif, Preset: 255
- ◆ IR LED: 6 pcs, IR Range: 80M
- ◆ Built-in PoE Optional(add \$12)
- ◆ Pan Range: 355°, Pan Speed: Max 90°/sec
- ◆ Tilt Range: 90°, Tilt Speed: Max 90°/sec
- ◆ Video Compression: H.265 Main Profile, MJPEG/JPEG Baseline
- ◆ Power Supply: DC 12V include
- ◆ Size: 130mm x 130mm x 210mm
- ◆ Weight: 3.2KG



Specification:

MODEL NO.	VNP-CMV20X20HD	VNP-CMV20X50HD
Description	4.5" IP66 Medium Speed PTZ Camera;IR Led: 6pcs, IR Range: 80M	
TV System	NTSC / PAL	
Image Sensor	1/3" GK7205 + SONY IMX307 Starlight 2.0 Mega Pixels CMOS, Low Illumination	1/3" GK7205 + SONY IMX335 5.0 Mega Pixels CMOS, Low Illumination
Resolution	1080P	5MP
Effective Pixels	1920(H) × 1080(V)	2592(H)×1944(V)
Lens	20X Optical Zoom (4.7-84.6mm Lens)	20X Optical Zoom (4.7-84.6mm Lens)
Minimum illumination	0.01Lux @(F1.6,AGC ON) ,0 Lux with IR	
Video interface	RJ45	
Video compression	H.265	
Video bit rate	32kbps-16Mbps	
Day and night conversion	IR-Cut	
PTZ Control	PTZ keyboard controller	
Electronic shutter	1/25s ~ 1/100000s	
D-WDR	Support	
DNR	2D/3D-DNR	
Image direction	Mirror/ Flip	
Privacy zone	Support	
Mobile detection	Support	
Horizontal range	0°~355°	
Vertical range	0°~90°	
Horizontal speed	30°/ s	
Vertical speed	30°/ s	
Presets	255	
Cruise track	8 groups, each group for 16 presets	
Patrol track	4 groups, each group record 3 mins	
POE	Optional	
ONVIF	Support	
Waterproof level	IP66	
Bracket	Wall mounted	
Size	130mm x 130mm x 210mm	
Weight	3.2 kg	
Power	DC12V	
Work temperature	-30℃~60℃	
Vandsec Electronics Limited http://www.vandsec.com Email: info@vandsec.com		