

Features:

- ◆ 2.5" Waterproof Semi-Metal IP66 4G IP Mini Speed PTZ Camera
- ◆ Pan Range: 355°, Pan Speed: Max 30°/sec
- ◆ Tilt Range: 90°, Tilt Speed: Max 30°/sec
- ◆ IR & White LED: 10pcs, IR Range: 30M
- ◆ Support TF Card upto 128G, 3G/4G small Sim card(America add \$8.5, Japan add
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ H.265 video compression, video Push, QR Scan or download app (camhipro)
- ◆ Wifi connect by scan QR codes, smart key easily, radar scanning
- ◆ Built in PIR Alarm, Push alarm to smart phone
- ◆ Working Temperature: -10℃~+60℃
- ◆ Size: 110mm x 160mm x 220mm
- ◆ Power: 12V 1000MA power adapter include
- ◆ Weight: 1200g



Specifications:

Model	VN-GBG20	VN-GBG50	VN-GBG5X50	VN-GBG20-G	VN-GBG50-G	VN-GBG5X50-G
Description	2.5" Waterproof Semi-Metal IP66 4G/wifi IP Mini Speed PTZ Camera, IR & White LED: 10pcs, IR Range: 30M					
TV System	NTSC / PAL					
Video Output	WIFI			4G		
Resolution	2.0 Megapixel, T31L+GC2083 CMOS Sensor	5.0 Megapixel, T31X+SC5238 CMOS Sensor	5.0 Megapixel, T31X+SC5238 CMOS Sensor	2.0 Megapixel, T31L+GC2083 CMOS Sensor	5.0 Megapixel, T31X+SC5238 CMOS Sensor	5.0 Megapixel, T31X+SC5238 CMOS Sensor
Effective Pixels	1920(H) × 1080(V)	2560(H) × 1920(V)	2560(H) × 1920(V)	1920(H) × 1080(V)	2560(H) × 1920(V)	2560(H) × 1920(V)
Minimum Illumination	0.001Lux					
Day/Night	IR cut filter with auto switch, IR sensor					
Network	10/100M adaptation					
Video Compression	H.265 compression					
Pan Range	0-355°					
Tilt Range	0-90°					
Pan Speed	Max30°/sec					
Tilt Speed	Max 30°/sec					
Preset	128					
Support SD Card	YES (MAX Support 128G, over 32GB need FAT32 Format)					
User Permission	Multi-user Classification Management					
Power	12V 2000MA power adapter include					
Consumption	3.0W					
Lens	Board Lens 3.6mm	Board Lens 3.6mm	5x Optical Zoom(2.7-13.5mm Lens)	Board Lens 3.6mm	Board Lens 3.6mm	5x Optical Zoom(2.7-13.5mm Lens)
Size (mm)	110mm x 160mm x 220mm					
Weight (kg)	1.2 kg					
Temperature	-10℃~+60℃					
Humidity	0%-90%					
Vandsec Electronics Limited http://www.vandsec.com Email: info@vandsec.com						