

Features:

- ◆ 2.5" Waterproof Metal IP66 4G IP Mini Speed PTZ Camera
- ◆ Pan Range: 355°, Pan Speed: Max 30°/sec
- ◆ Tilt Range: 90°, Tilt Speed: Max 30°/sec
- ◆ 12pcs White Leds, IR Range: 35M
- ◆ TF Card local Storage (Max.128G,over 32GB need FAT32 Format)
- ◆ Support 3G/4G small Sim card (America or Japan 4G add \$5)
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ Preset: 128, App (camhipro)
- ◆ Video Compression: H.265 Main Profile; MJPEG/JPEG Baseline
- ◆ Working Temperature: -10℃~ +60℃
- ◆ Size: 175mm x 150mm x 105mm
- ◆ Power: 12V 2000MA power adapter include
- ◆ Weight: 1.5KG



Specifications:

Model	VN-GBM5X20-G	VN-GBM10X20-G	VN-GBM5X50-G	VN-GBM10X50-G
Description	2.5" Waterproof IP66 4G IP Mini Speed PTZ Camera,12pcs White Leds, IR Range: 35M			
TV System	NTSC / PAL			
Connection method	3G/4G			
Resolution	2.0 MegaPixels CMOS GK7205V200+SC2335 1080P@ 25fps(PAL), 30fps(NTSC)		5.0 MegaPixels CMOS GK7205V300+IMX335 5MP@ 25fps(PAL), 30fps(NTSC)	
Effective Pixels	1920(H) × 1080(V)		2560(H) × 1920(V)	
Lens	5x Optical Zoom(2.7-13.5mm Lens)	10x Optical Zoom(5-50mm Lens)	5x Optical Zoom(2.7-13.5mm Lens)	10x Optical Zoom(5-50mm Lens)
Minimum Illumination	0.001Lux			
Day/Night	IR cut filter with auto switch, IR sensor			
Network	10/100M adaptation ,3G/4G Network signal			
Video Compression	H.265 compression			
Audio processing	G.711A decoding standard, Audio Optional			
TF Card	Max.128G,over 32GB need FAT32 Format			
Pan Range	0°-355°			
Tilt Range	0°-90°			
Pan Speed	Max 30°/sec			
Tilt Speed	Max 30°/sec			
Preset	128			
Power/Current	12V 2000MA power adapter include			
Consumption	3.0W			
Size(mm)	175mm × 150mm × 105mm			
Weight (kg)	1.5 kg			
Temperature	-10℃~+60℃			
Humidity	0%-90%			
Vandsec Electronics Limited http://www.vandsec.com Email: info@vandsec.com				