

## Features:

- ◆ 3.5" Waterproof Semi-Metal IP66 4G/wifi IP Speed PTZ Camera
- ◆ Pan Range: 355°, Pan Speed: Max 30°/sec
- ◆ Tilt Range: 90°, Tilt Speed: Max 30°/sec
- ◆ IR & White LED: 12pcs, IR Range: 30M
- ◆ Support TF Card upto 128G, 3G/4G small Sim card(America add \$8.5, Japan add \$15)
- ◆ PNP(Plug and Play), support smart phone & tablets
- ◆ H.265 video compression, video Push, QR Scan or download app (camhipro)
- ◆ Wifi connect by scan QR codes, smart key easily, radar scanning
- ◆ Red and blue light alert, Push alarm to smart phone
- ◆ Working Temperature: -10°C~ +60°C
- ◆ Size: 115mm x 165mm x 220mm
- ◆ Power: 12V 1000MA power adapter include
- ◆ Weight: 1800g



## Specifications:

Model	VN-GBR5X20	VN-GBR5X50	VN-GBR10X20	VN-GBR10X50	VN-GBR5X20-G	VN-GBR5X50-G	VN-GBR10X20-G	VN-GBR10X50-G	VN-GBR80-G	VN-GBR5X80-G
Description	3.5" Waterproof Semi-Metal IP66 4G/wifi IP Speed PTZ Camera · IR & White LED: 12pcs, IR Range: 30M									
TV System	NTSC / PAL									
Video Output	WIFI					4G				
Resolution	2.0 Megapixel, T31L+GC2083 CMOS Sensor	5.0 Megapixel, T31X+SC5238 CMOS Sensor	2.0 Megapixel, T31L+GC2083 CMOS Sensor	5.0 Megapixel, T31X+SC5238 CMOS Sensor	2.0 Megapixel, T31L+GC2083 CMOS Sensor	5.0 Megapixel, T31X+SC5238 CMOS Sensor	2.0 Megapixel, T31L+GC2083 CMOS Sensor	5.0 Megapixel, T31X+SC5238 CMOS Sensor	8.0 Megapixel, SSC338Q+IMX415 CMOS Sensor	8.0 Megapixel, SSC338Q+IMX415 CMOS Sensor
Effective Pixels	1920(H) × 1080(V)	2560(H) × 1920(V)	1920(H) × 1080(V)	2560(H) × 1920(V)	1920(H) × 1080(V)	2560(H) × 1920(V)	1920(H) × 1080(V)	2560(H) × 1920(V)	3840(H) × 2160(V)	3840(H) × 2160(V)
Minimum Illumination	0.001Lux									
Day/Night	IR cut filter with auto switch, IR sensor									
Network	10/100M adaptation									
Video Compression	H.265 compression									
Pan Range	0-355°									
Tilt Range	0-90°									
Pan Speed	Max30°/sec									
Tilt Speed	Max 30°/sec									
Preset	128									
Support SD Card	YES (MAX Support 128G, over 32GB need FAT32 Format)									
User Permission	Multi-user Classification Management									
Power	12V 2000MA power adapter include									
Consumption	4.0W									
Lens	5x Optical Zoom(2.7-13.5mm Lens)	5x Optical Zoom(2.7-13.5mm Lens)	10x Optical Zoom(4.7-47mm)	10x Optical Zoom(4.7-47mm)	5x Optical Zoom(2.7-13.5mm Lens)	5x Optical Zoom(2.7-13.5mm Lens)	10x Optical Zoom(4.7-47mm)	10x Optical Zoom(4.7-47mm)	Lens: Board Lens 3.6mm	5x Optical Zoom(2.7-13.5mm Lens)
Size (mm)	115mm x 165mm x 220mm									
Weight (kg)	1.8 kg									
Temperature	-10°C~+60°C									
Humidity	0%-90%									
Vandsec Electronics Limited   <a href="http://www.vandsec.com">http://www.vandsec.com</a>   Email: <a href="mailto:info@vandsec.com">info@vandsec.com</a>										